



Declaration of Conformity – Number 001/04/G

***Hamberger Industrierwerke GmbH, PO Box 100353,
D-83003 Rosenheim***

hereby declare that the construction product

Celenio

produced in the Rosenheim plant,

- for the interior use as building component in dry areas,
- as non-load bearing component with glue-down installation,
- with the following features/properties*):

Thickness	<i>8 mm</i>
Raw unit weight	<i>1,100 kg/m³</i>
Fire protection	<i>C_{FI} - s1</i>
Formaldehyde class	<i>E1</i>

corresponds with EN 13986, Annex ZA

HAMBERGER Industrierwerke GmbH

ppa.

Dr. Matthes

Dr. Lars Matthes

Stephanskirchen February 25th 2005

*) see back side:

The outlined fire related characteristics are only valid

- where the installation has been carried out in accordance with the manufacturer's instructions and with the exclusive use of
- Celenio Special Glue,
- Celenio Special Grout

Evidence of conformity of **reaction to fire with DIN EN 13 501-1** established by:

MPA Stuttgart · Otto-Graf-Institute
Materials Testing Institute · University of Stuttgart
Fire Protection Dept. · Fire Classification of Building Materials
Pfaffenwaldring 4 · D-70569 Stuttgart, Germany
ID No. 0672

Evidence of conformity of **formaldehyde release with DIN EN 717-1** established by:

Fraunhofer-Institute for Wood Research
Wilhelm-Klauditz-Institut WKI
Bienroder Weg 54 E · D-38108 Braunschweig, Germany
ID No. 0765

Further applicable standards:

- **DIN EN 13893** Resilient, laminate and textile floor coverings; Measurement of dynamic coefficient of friction on dry floor surfaces
- **DIN EN 12524** Building materials and products; Hygrothermal properties; Tabulated design values