



Declaration of Conformity – Number 027/11

***Hamberger Flooring GmbH & Co. KG, PO Box 100353,
D-83003 Rosenheim***

hereby declare that the construction product

HARO Tritty Laminate Floor 100

produced in the Rosenheim plant,

for use in the building industry, for the interior use as non-load bearing building component in dry areas with the following features/properties*):

Thickness:	<i>8 mm</i>
Substance:	<i>7.3 kg/m²</i>
Fire protection:	<i>C_{fl} - s1</i>
Formaldehyde class:	<i>E1</i>
Slip resistance:	<i>DS</i>
Thermal resistance	<i>0.068 m²K/W</i>
Antistatic behaviour:	<i>< 2 kV</i>

corresponds with EN 14041, Annex ZA

Hamberger Flooring GmbH & Co. KG

Peter Hamberger

Stephanskirchen, 05 September 2011

Evidence of conformity of **reaction to fire with DIN EN 13 501-1** and of **formaldehyde release with DIN EN 717-1** established by:

A) MPA Stuttgart · Otto-Graf-Institut

Materialprüfungsanstalt · Universität Stuttgart
Abteilung Brandschutz · Brandverhalten von Baustoffen
Pfaffenwaldring 4 · 70569 Stuttgart
Notified Body number : 0672

B) Exova GmbH

Industriepark Höchst, C 369
65926 FRANKFURT AM MAIN
Notified Body number : 1378

C) eco-Institut GmbH

Sachsenring 69
50677 Köln
Notified Body number : 2097

D) Fraunhofer-Institut . Holzforschung

Wilhelm Klauditz-Institut . WKI
Bienroder Weg 54 E . 38108 Braunschweig
Notified Body number : 0765

E) TÜV Rheinland LGA Bautechnik GmbH

Tillystrasse 2
90431 Nürnberg
Notified Body number : 0780

Further applicable standards:

- **DIN EN 13893** Resilient, laminate and textile floor coverings; Measurement of dynamic coefficient of friction on dry floor surfaces
- **DIN EN 12524** Building materials and products; Hygrothermal properties; Tabulated design values
- **DIN EN 1815** Resilient and textile floor coverings; Assessment of static electrical propensity