



Declaration of Conformity – Number 030/08

*Hamberger Flooring GmbH & Co. KG, PO Box 100353,
D-83003 Rosenheim*

hereby declare that the construction product

REX Laminate Floor domus

produced in the Rosenheim plant,

for use in the building industry, for the interior use as non-load bearing building component in dry areas with the following features/properties*):

Thickness:	7 mm
Substance:	6.6 kg/m ²
Fire protection:	C _{fl} - s1
Formaldehyde class:	E1
Slip resistance:	NPD
Thermal resistance	0.063 m ² K/W

corresponds with EN 14041, Annex ZA

Hamberger Flooring GmbH & Co. KG

Peter Hamberger

Stephanskirchen, 03 November 2008

*) see back side:

Evidence of conformity of **reaction to fire with DIN EN 13 501-1** established by:

MPA Stuttgart · Otto-Graf-Institute
Materials Testing Institute · University of Stuttgart
Fire Protection Dept. · Fire Classification of Building Materials
Pfaffenwaldring 4 · D-70569 Stuttgart, Germany
ID No. 0672

Evidence of conformity of **formaldehyde release with DIN EN 717-1** established by:

Fraunhofer-Institute for Wood Research
Wilhelm-Klauditz-Institut (WKI)
Bienroder Weg 54 E · D-38108 Braunschweig, Germany
ID No. 0765

Further applicable standards:

- **DIN EN 13893** Resilient, laminate and textile floor coverings; Measurement of dynamic coefficient of friction on dry floor surfaces
- **DIN EN 12524** Building materials and products; Hygrothermal properties; Tabulated design values