



Declaration of Conformity – Number 043/09

***Hamberger Flooring GmbH & Co. KG, PO Box 100353,
D-83003 Rosenheim***

hereby declare that the construction product

REX Parquet 25 12mm

produced in the Rosenheim plant,

for internal installation other than high moisture content areas in the building industry, over subfloor installation, with the following features/properties^{*)}:

Thickness:	<i>12 mm</i>
Density:	<i>> 500 kg/m³</i>
Fire protection:	<i>D_{FI} - s1</i>
Formaldehyde class:	<i>E1</i>
Thermal resistance	<i>0.098 m²K/W</i>

corresponds with EN 14342, Annex ZA

Hamberger Flooring GmbH & Co. KG

Peter Hamberger

Stephanskirchen 21 September 2009

^{*)} see back side

Evidence of conformity of **reaction to fire with DIN EN 14 342**
chart 1 (CWFT).

Evidence of conformity of **formaldehyde release with DIN EN 717-1** established by:

Fraunhofer-Institute for Wood Research
Wilhelm-Klauditz-Institut WKI

Bienroder Weg 54 E · D-38108 Braunschweig, Germany

ID No. 0765

Further applicable standards:

- **DIN EN 12524** Building materials and products; Hygrothermal properties; Tabulated design values