



Declaration of Conformity – Number 044/09

***Hamberger Flooring GmbH & Co. KG, PO Box 100353,
D-83003 Rosenheim***

hereby declare that the construction product

REX Parquet 40 13.5mm

produced in the Rosenheim plant,

for internal installation other than high moisture content areas in the building industry, over subfloor installation, with the following features/properties*):

Thickness:	<i>13.5 mm</i>
Density:	<i>> 500 kg/m³</i>
Fire protection:	<i>≥ D_{F1} - s1^{**})</i>
Formaldehyde class:	<i>E1</i>
Thermal resistance	<i>0.11 m²K/W</i>

corresponds with EN 14342, Annex ZA

Hamberger Flooring GmbH & Co. KG

Peter Hamberger

Stephanskirchen 22 September 2009

^{*)}, ^{**}) see back side:

****)** **Reaction to fire** (individual verification)
C_{FI}-s1 in the wood species "Achateiche" (oak), varnished.

Evidence of conformity of **reaction to fire with DIN EN 14 342**
chart 1 (CWFT).

Evidence of conformity of **reaction to fire with DIN EN 13 501-1**
established by:

MPA Dresden GmbH
Fuchsmühlenweg 6F * 09599 Freiberg
Ident-No. 0767

Evidence of conformity of **formaldehyde release with DIN EN**
717-1 established by:

Fraunhofer-Institute for Wood Research
Wilhelm-Klauditz-Institut WKI
Bienroder Weg 54 E * D-38108 Braunschweig, Germany
ID No. 0765

Further applicable standards:

- **DIN EN 12524** Building materials and products; Hygrothermal properties; Tabulated design values