



Declaration of Conformity – Number 006/05

***Hamberger Industrierwerke GmbH, PO Box 100353,
D-83003 Rosenheim***

hereby declare that the construction product

HARO Tritty Laminate Floor 75

produced in the Rosenheim plant,

- for use in the building industry,
for the interior use as non-load bearing building
component in dry areas
- with the following features/properties*):

Thickness:	<i>7 mm</i>
Substance:	<i>6.6 kg / m²</i>
Fire protection:	<i>C_{FI} - s1</i>
Formaldehyde class:	<i>E1</i>
Slip resistance:	<i>NPD</i>
Thermal resistance	<i>0.063 m²K/W</i>

corresponds with EN 14041, Annex ZA

HAMBERGER Industrierwerke GmbH

ppa.

Dr. Lars Matthes

Stephanskirchen June 15th 2005

*) see back side:

Evidence of conformity of **reaction to fire with DIN EN 13 501-1** established by:

MPA Stuttgart · Otto-Graf-Institute
Materials Testing Institute · University of Stuttgart
Fire Protection Dept. · Fire Classification of Building Materials
Pfaffenwaldring 4 · D-70569 Stuttgart, Germany
ID No. 0672

Evidence of conformity of **formaldehyde release with DIN EN 717-1** established by:

Fraunhofer-Institute for Wood Research
Wilhelm-Klauditz-Institut (WKI)
Bienroder Weg 54 E · D-38108 Braunschweig, Germany
ID No. 0765

Further applicable standards:

- **DIN EN 13893** Resilient, laminate and textile floor coverings; Measurement of dynamic coefficient of friction on dry floor surfaces
- **DIN EN 12524** Building materials and products; Hygrothermal properties; Tabulated design values