

# Declaration of Conformity (CE)

This is to declare that building product Kronopol/Kronoply OSB 3 and Kronopol/Kronoply OSB 4

**CE 1034- CPD- 1276/6/04 EN 13986, EN 300 OSB 3, EI, D-s2, dO < 5 ppm, 8 – 25 mm**  
**CE 1034- CPD- 1276/7/04 material for floor decking (Flooring) EN 13986, EN 300 OSB 3, EI, D-s2, dO < 5 ppm**  
**CE 1034- CPD- 1276/9/04 material for roof decking (Roofing) EN 13986, EN 300 OSB 3, EI, D-s2, dO < 5 ppm**  
**CE 1034- CPD- 1276/6/04 EN 13986, EN 300 OSB 4, EI, D-s2, dO < 5 ppm, 8 – 25 mm**  
**CE 1034- CPD- 1276/8/04 material for floor decking (Flooring) EN 13986, EN 300 OSB 4, EI, D-s2, dO < 5 ppm**  
**CE 1034- CPD- 1276/10/04 material for roof decking (Roofing) EN 13986, EN 300 OSB 4, EI, D-s2, dO < 5 ppm**  
**CE 1034- CPD- 1276/11/04 material for roof decking (Wall) EN 13986, EN 300 OSB 4, EI, D-s2, dO < 5 ppm**

is suitable for application in building industry for indoors use as a bearing building unit in a dry and wet area, respectively, within a range of rated thickness between 8 and 25 mm.

**Manufacturer herein declares that the two named below groups of product meet all requirements of EEC Directive 93/68 in conformity with the standard EN 13986:2002 enclosure ZA.**

We confirm that 2 groups of product OSB 3 and OSB 4 fulfill the following requirements:

**EN 13986 table 1 and table 2**

in conformity with EN 300 OSB3 and OSB4, E 1, D-s2 of rated thickness between 8 and 25 mm.

**EN 13986 table 7 concerning indoors application as a bearing blind floor on floor joists**

in conformity with EN 300 OSB3 and OSB4, E 1, D-s2/DFL s1, for the rated thickness range from 12 mm and support spacing up to 0,625 m

**EN 13986 table 7 concerning indoors application as a roof sheathing on beams**

in conformity with EN 300 OSB3, E 1, D-s2,  
for the rated thickness range from 15 mm and support spacing up to 0,8 m  
for the rated thickness range from 18 mm and support spacing up to 1,25 m

**EN 13986 table 7 concerning indoors application as a roof sheathing on beams**

in conformity with EN 300 OSB4, E 1, D-s2,  
for the rated thickness range from 15 mm and support spacing up to 0,8 m  
for the rated thickness range from 18 mm and support spacing up to 1,0 m

**EN 13986 table 7 concerning indoors application as a Wall frame in conformity with EN 300 OSB4, E 1, D-s2,**  
for the rated thickness range from 9 mm

Application of these 2 groups was determined on the basis of following standards:

<b>EN 1058/EN 789</b>	Characteristic Strength, stiffness and density for structural design
<b>EN 1195/EN 12871</b>	Guidance of installation Flooring-Structural floor decking on joists
<b>EN 12871</b>	Guidance of installation Roofing-Structural roof decking on joists

The Working Group of European Union registered at number 1034 HFB in Leipzig verified the in-house production control of products enlisted here.

Number of certificate:

**CPD-1276/6/04 CPD-1276/7/04 CPD-1276/8/04 CPD-1276/9/04 CPD-276/10/04 CPD-276/11/04**

Notified Body: **1034**

Żary, 07.01.2005

Kronopol Ltd.  
ul. Serbska 56,  
68-200 Żary, Poland

R. Kamiński, Manager of Quality Management:

signature

Dr J. Hasch (CTO Board of Directors):

signature